

# IP-200H

## Polypropylene Impact Copolymer

**IP-200H** is a certified prime resin for injection molding applications needing Medium Impact Performance. **IP-200H** is designed for products that require Long-Term Heat-Aging resistance.

PROPERTIES	ASTM	UNIT	NOMINAL VALUES
<b>PHYSICAL</b>			
Melt Flow Rate (230°C, 2.16kg)	D1238	g/10 min	20
Density	D1505	g/cm <sup>3</sup>	0.900
<b>MECHANICAL</b>			
Flexural Modulus <sup>1</sup> (1% Secant)	D790	psi	175k
Tensile Strength @ Yield <sup>2</sup>	D638	psi	3900
Notched Izod Impact (73°F)	D256	ft-lb/in	1.7

Typical Value of Properties not to be construed as specifications

- 1 - @ 0.051 in/min
- 2 - @ 2 in/min.



The technical information, suggested uses and applications presented are made without charge and are believed to be reliable; however, the Ravago Group\* disclaims responsibility for reliance and results of use of this information. THE RAVAGO GROUP DISCLAIMS ALL WARRANTIES, EXPRESSED OR IMPLIED, CONCERNING THE PRODUCT(S) DESCRIBED HEREINABOVE, INCLUDING ANY WARRANTIES OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE. The Ravago Group expressly disclaims any statements or suggestions as being inducement. All users should rely upon their own knowledge and testing in determining product suitability.