

HP-020

Polypropylene Homopolymer

HP-020 is a Homopolymer certified prime grade designed for extrusion of sheet for thermoforming processes. **HP-020** contains a nucleating agent featuring high clarity and excellent melt strength. **HP-020** complies with FDA regulation 21CFR 177.1520(c) 3.2a concerning the Polypropylene use in contact with food articles.

PROPERTIES	ASTM	UNIT	NOMINAL VALUES
RESIN			
Density	D1505	g/cm	0.903
Melt Flow Rate (190 °C, 2.16kg)	D1238	g/10 min	2.0
FILM			
Flexural Modulus - 1% Secant (Inj) ²	D790	psi	230k
Tensile Strength @ Yield* ¹	D638	psi	5100
Elongation @ Yield* ¹	D638	%	10
IMPACT/HARDNESS			
Notched Izod Impact*	D256A	ft-lb/in	1.3
Deflection Temperature Under Load (66psi Unannealed)	D648	°F	217
Vicat Softening Temperature	D1525	°F	293

Typical Value of Properties not to be construed as specifications

- 1 - 2.0 in/min
- 2 - 0.051 in/min



The technical information, suggested uses and applications presented are made without charge and are believed to be reliable; however, the Ravago Group* disclaims responsibility for reliance and results of use of this information. THE RAVAGO GROUP DISCLAIMS ALL WARRANTIES, EXPRESSED OR IMPLIED, CONCERNING THE PRODUCT(S) DESCRIBED HEREINABOVE, INCLUDING ANY WARRANTIES OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE. The Ravago Group expressly disclaims any statements or suggestions as being inducement. All users should rely upon their own knowledge and testing in determining product suitability.