



18F1H- LINEAR LOW-DENSITY POLYETHYLENE RESIN

Shell Polymers LLDPE 18F1H is a 1-hexene blown film resin.

Product Family

LLDPE

Conversion Process

Film Extrusion

Highlights

- Produces films that have
 - outstanding tensile, stiffness and toughness properties
- Designed to be used in
 - demanding packaging applications
 - Gas phase technology

Additives

Thermal stabilizer



Ensuring Lot-to-Lot Consistency

Within our innovation center, the analytical laboratory helps us produce highly consistent product. For example: The lab's data helps us to get as close as possible to the center of the specification range and to ensure all railcars are near that range.



Convenient Pennsylvania Location

Our accessible Pennsylvania location is within 700 miles of most North American polyethylene buyers, so small- to large-sized converters like you can travel to our plant, collaborate with our team and get home the same day. Read more about how our location delivers a logistical advantage.



In-Depth Film Studies

In the material testing and inspection laboratory, we conduct a wide range of in-depth studies that characterize the mechanical, processing and visual properties of a polymer. Such tests include film testing for tensile, impact and tear strength as well as coefficient of friction and cling.

Product Details

Melt Index	Method	Test Conditions
1.0	ASTM D1238 (g/10min)	2.16 kg/190C

Density	Method
0.918	ASTM D792 (g/cm3)